

Name `delete-domain` – deletes a domain

Synopsis `delete-domain [--help] [--domaindir domaindir domain_name]`

Description The `delete-domain` subcommand deletes the specified domain. The domain must already exist and must be stopped.

This subcommand is supported in local mode only.

Options `--help`

`-?`

Displays the help text for the subcommand.

`--domaindir`

The directory where the domain to be deleted is located. If specified, the path must be accessible in the file system. If not specified, the domain in the default *install-dir/domains* directory is deleted.

Operands `domain_name` The unique name of the domain you want to delete.

Examples **EXAMPLE 1** Deleting a Domain

This example deletes a domain named `mydomain4` from the default domains directory.

```
asadmin> delete-domain mydomain4
Domain mydomain4 deleted.
Command delete-domain executed successfully.
```

EXAMPLE 2 deleting a Domain From an Alternate Location

This example deletes a domain named `sampleDomain` from the `/home/someuser/domains` directory.

```
asadmin> delete-domain --domaindir /home/someuser/domains sampleDomain
Domain sampleDomain deleted
Command delete-domain executed successfully.
```

Exit Status 0 subcommand executed successfully

1 error in executing the subcommand

See Also `create-domain(1)`, `start-domain(1)`, `stop-domain(1)`, `list-domains(1)`

[asadmin\(1M\)](#)