

Name restart-domain– restarts the DAS of the specified domain

Synopsis restart-domain [--help] [--domaindir *domain-dir*] [*domain-name*]

Description The restart-domain subcommand stops and then restarts the Domain Administration Server (DAS) of the specified domain. If a domain is not specified, the default domain is assumed. If there are two or more domains, the *domain-name* operand must be specified. If the server is not already running, you are asked if you want to start it.

The restart-domain subcommand does not exit until the subcommand has verified that the domain has been stopped and restarted.

A domain can also be restarted by using the start-domain subcommand with the --verbose option set to true. In this situation, after the domain is restarted, messages continue to be displayed in the console window that was opened when the domain was originally started.

This subcommand is supported in local mode only.

Options --help

-?

Displays the help text for the subcommand.

--domaindir

The directory of the domain that is to be restarted. If specified, the path must be accessible in the file system. If not specified, the domain in the default *as-install/glassfish/domains* directory is restarted.

Operands *domain-name* The name of the domain you want to restart. Default is the name specified during installation, usually domain1.

Examples EXAMPLE 1 Restarting a Domain

This example restarts mydomain4 in the default domains directory.

```
asadmin> restart-domain mydomain4
```

```
Successfully restarted the domain
```

```
Command restart-domain executed successfully.
```

Exit Status 0 subcommand executed successfully

1 error in executing the subcommand

See Also delete-domain(1), list-domains(1), start-domain(1), stop-domain(1)

[asadmin\(1M\)](#)