

Name create-jdbc-resource– creates a JDBC resource with the specified JNDI name

Synopsis create-jdbc-resource [--help]
--connectionpoolid *connectionpoolid*
[--enabled={false|true}]
[--description *description*]
[--property (*property=value*)[:*name=value*]*]
[--target *target*]
jndi_name

Description The create-jdbc-resource subcommand creates a new JDBC resource.

This subcommand is supported in remote mode only.

Options --help
-?
Displays the help text for the subcommand.

--connectionpoolid
The name of the JDBC connection pool. If two or more JDBC resource elements point to the same connection pool element, they use the same pool connection at runtime.

--enabled
Determines whether the JDBC resource is enabled at runtime. The default value is true.

--description
Text providing descriptive details about the JDBC resource.

--property
Optional attribute name/value pairs for configuring the resource.

--target
Do not specify this option. This option is retained for compatibility with other releases. If you specify this option, a syntax error does not occur. Instead, the subcommand runs successfully and the option is silently ignored.

Operands *jndi_name*
The JNDI name of this JDBC resource.

Examples **EXAMPLE 1** Creating a JDBC Resource

This example creates a JDBC resource named jdbc/DerbyPool.

```
asadmin> create-jdbc-resource  
--connectionpoolid sample_derby_pool jdbc/DerbyPool  
Command create-jdbc-resource executed successfully.
```

Exit Status 0 subcommand executed successfully
1 error in executing the subcommand

See Also `delete-jdbc-resource(1)`, `list-jdbc-resources(1)`
`asadmin(1M)`

