

Name update-connector-work-security-map– modifies a work security map for the specified resource adapter

Synopsis update-connector-work-security-map [--help]
--rename *raname*
[--addprincipals eis-principal1=*server-principal1*[, eis-principal2=*server-principal2*]*]
[--addgroups eis-group1=*server-group1*[, eis-group2=*server-group2*]*]
[--removeprincipals *eis-principal1*[,*eis-principal2*]*]
[--removegroups *eis-group1*[, *eis-group2*]*]
mapname

Description The update-connector-work-security-map subcommand modifies a security map for the specified resource adapter.

This subcommand is supported in remote mode only.

Options --help
-?
Displays the help text for the subcommand.
--rename
Indicates the connector module name with which the work security map is associated.
--addprincipals
Specifies a comma-separated list of EIS-specific principals to be added. Use either the --addprincipals option or the --addgroups option, but not both.
--addgroups
Specifies a comma-separated list of EIS groups to be added. Use either the --addprincipals option or the --addgroups option, but not both.
--removeprincipals
Specifies a comma-separated list of EIS-specific principals to be removed.
--removegroups
Specifies a comma-separated list of EIS groups to be removed.

Operands *mapname*
The name of the work security map to be updated.

Examples **EXAMPLE 1** Updating a Connector Work Security Map

This example updates workSecurityMap2 by removing eis-group-2.

```
asadmin> update-connector-work-security-map  
--rename my-resource-adapter --removegroups eis-group-2 workSecurityMap2  
Command update-connector-work-security-map executed successfully.
```

Exit Status 0 subcommand executed successfully
1 error in executing the subcommand

See Also create-connector-work-security-map(1), delete-connector-work-security-map(1),
list-connector-work-security-maps(1)

[asadmin\(1M\)](#)

